

## Soft Touch Wall Putty

**Colour:** White

**Shelf life:** 10-12 Months

**Surface Drying time :** 40 Mins

**Pot life:** > 80 Min

**Coverage:** 10- 15 Sq. Ft/Kg (Depending on the finish of the Wall)

**Recommended Mixing:** 300 - 450 ml of water for 1 kg of Wall Putty

**Recoat Time:** Drying time for recoat is 6 to 8 hours.


### Benefits:

- Reduces paint consumption
- Avoid frequent repainting
- Cost effective
- Protects from algae on wall
- Good intercoat adhesion to emulsion paints
- Protects expensive paint from dampness, peeling off, flaking
- Suitable for interior as well as exterior walls

### Features:

- Pure White in colour
- Has good resistance to water
- Provide smooth & uniform finish
- Odourless & anti-fungal
- Best Adhesiveness & durability
- Easy to apply
- True color tone of the paint is maintained



 Water Resistant

**Soft Touch**

\*All Soft Paint products contain no added Lead, Mercury, Arsenic or Chromium

### Surface Preparation



#### PLASTER

New Surfaces must be allowed to cure completely for 15 days.



#### CLEANING

Clean loose particles, dirt, grease and traces of foreign material from the surface, if necessary by using sand paper or by chipping. For loose Plaster areas, remove the defective material and re-plaster the area.



#### FILLING FOR CRACKS

Fill up any cracks in base plaster by using any crack filler.



#### FILLING FOR HOLES & DENTS

Incase of dents and Holes use white cement to level it up.



#### PRE WETTING

Pre wet the surface with water before application of 1st coat of filling putty

### PACKAGING



Shelf Life : 10 to 12 months if stored in a cool and dry location. As temperature, humidity, water addition, and other parameters vary from site to site.

### Application Process

#### STEP 1 SANDING

SAND THE WALL PUTTY SURFACE WITH EMERY PAPER 180 AND WIPE CLEAN

#### STEP 2 PRE WET THE SURFACE

PRE WET THE SURFACE BEFORE APPLICATION OF 1ST COAT OF SOFT TOUCH WALL PUTTY

#### STEP 3 FIRST COAT KNIFE / TROWEL

APPLY COAT OF 1.5 THICKNESS MAX.

#### STEP 4 SECOND COAT KNIFE / TROWEL

APPLY COAT OF 0.5 THICKNESS MAX.

#### STEP 5 PRIMER AND EMULSION COAT


APPLY A COAT OF PRIMER FOLLOWED BY 2-3 COATS OF EMULSION

### COVERAGE

On rough masonry surface by putty knife



**10 - 15sq.ft/kg**  
for upto 2mm  
thickness in 2 coats



It can be used on all types of exterior cement plasters/interior walls, asbestos sheets, concrete etc